

# Material Safety Data Sheet According to 91/155/EEC and ISO 11014-1

# 1. IDENTIFICATION OF SUBSTANCE

Product Name: Iron Oxide Black

Company Name: Yuxing Pigment Co.,Ltd Manufacturer Name: Yuxing Pigment Co.,Ltd

Telephone: 0086-0510-87226777

#### 2. COMPOSITION/DATA ON COMPONENTS

Chemical characterization:

Synthetic iron oxide Fe<sub>3</sub>O<sub>4</sub>, C.I. Pigment BLACK 11, CAS. No. 1317-61-9

Dangerous components: None

Ingredient Content: Fe<sub>3</sub>O<sub>4</sub> 99%; Water 1%

#### 3. HAZARDS IDENTIFICATION

May cause mechanical irritation to the eyes, skin and respiratory tract, Irritating gases/fumes may be given off during burning or thermal decomposition.

HMIS Codes: H=0,F=0,R=0,P=0 (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

Eyes: Non-irritating to eyes. Excessive exposure to airborne dust may reduce visibility and/or cause unpleasant deposits.

Skin: will not irritate skin and is not likely to cause allergic skin reaction. Injury to the skin or mucus membranes can occur by direct mechanical action or by rigorous skin cleaning necessary for removal of dust.

Other effects: none known.

Not a hazard in normal industrial use. No harmful effects observed.

The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC or amendments.

#### 4. FIRST AID MEASURES

First aid for skin: In case of skin contact, immediately flush skin with water. Wash clothing before reuse. Call a physician if irritation occurs.

First aid for ingestion: Immediately contact a physician.

First aid for eyes: Flush eyes with plenty of water, lifting lids periodically for at least 15 minutes. Consult a physician if irritation persists.

First aid for inhalation: Remove from dusty area to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

#### 5. FIRE FIGHTING MEASURES

Product is non-combistible.

Upper Explosive Limit(UEL): Will not explode.

Lower Explosive Limit(LEL): Will not explode.

Fire Fighting Instructions: Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes and smoke inhalation. Suitable extinguishing media: Material is not combustible. Use extinguishing media suitable for

other combustible materials in the area.

Special hazards caused by the material, its combustion products for resultant gases: none

Flash point: Not applicable.

Auto-ignition temperature: Not applicable.



# 江 苏 宇 星 科 技 有 限 公 司 YUXING PIGMENT CO., LTD

#### 6. ACCIDENTAL RELEASE MEASURES

Small spill: if dust is generated, use appropriate respiratory protection. Vacuum or scoop material into an appropriately marked container for re-use or disposal. Avoid excessive generation of dust. Large spill: Use recommend protective clothing and respiratory protection. Use shovel to reclaim material.

Vacuum or scoop material into an appropriately marked container for re-use or disposal. Avoid excessive generation of dust. Spill area can be washed with water. Collect wash water for approved disposal. Prevent runoff from entering storm sewers and ditches, which lead to natural waterways.

Environmental protection conduct: Do not sweep or wash into public stretches of water, sewers or sites of unknown discharge paths.

After spillage/leakage/gas leakage:

Clean up immediately with wetting or absorbent material avoiding dusting.

#### 7. HANDLING AND STORAGE

#### Storage:

Storage dry at ambient temperature away from food and beverages, excessive heat or flame sources (furnace, kilns, boilers etc.) store away form substances subject to catalytic decomposition by dust e.g. peroxides.

# Handling:

Usual precautions for nuisance dust should be observed.

Protection against fire and explosion:

The product is non-flammable

Flammability Class: not applicable

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional notes for design of plant equipment:

No further details, see sec. 7

Components with workplace-related limits to be monitored:

Designation	%	Type of data	Unit
Nuisance dust	100	MAK	6 mg/m <sup>3</sup>
		TLV/TWA(USA)	10 mg/m <sup>3</sup>

Additional protective measures: Eye wash stations and washing facilities should be available. Employees should wash their hands and face before eating, drinking or using tobacco products. Respiratory protection: An appropriate dust filter has to be used if a breathable dust is liberated. Eye protection requirements: Safety glasses are recommended.

Skin protection requirements: Rubber, cloth, or plastic gloves are recommended to reduce skin

Method

Lit.

contact where appropriate for job conditions.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: powder Color: black Odor: odorless

Change in physical state Thermal Decomposition:

Flash point: not flammable

Flammable properties: The product is not flammable under standardized conditions.

Explosion risks: The product is not explosive.

n.a.



# 江 苏 宇 星 科 技 有 限 公 司 YUXING PIGMENT CO., LTD

Specific Gravity: Greater than 1.

Viscosity: Not applicable.

Vapour pressure: Not applicable. n..a. mbcar

Density:  $(20^{\circ}\text{C})$  4.1 g/cm<sup>3</sup> DIN/ISO 787

part 10

В

Solubility in water:  $(20^{\circ})$  <0.5 % DIN/ISO 787

part 3

PH-Value: (at 100 g/l  $H_2O$ ) (20°C) ca.3.5-7 DIN/ISO 787

part 9

# 10. STABILITY AND REACTIVITY

Hazardous Polymerization: Will not occur.

Stability: Stable Material. Incompatibilities: None known. Instability conditions: None known.

Decomposition temperature: Greater than 120℃.

Decomposition products: None known.

#### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

LD50/oral/rat: Not tested. LD50/inhal/rat: Not tested. Sensitizing: None expected.

Primary skin irritation/rabbit: No data available.

Because of experiences with the product mentioned, there are on recognizable hazards for

human beings, if it is correctly used and applied.

# 12. ECOLOGICAL INFORMATIONS

Mobility: No data available. Degradability: No data available. Accumulation: No data available. Short and long term effects on:

Ecotoxicity: No data available.

Other adverse effects: No data available.

#### 13. DISPOSAL CONSIDERATIONS

Product: Material which can not be re-used should be disposed in according with federal, state and local environmental control regulations at an authorized site by an approved contractor. This product when discarded as sold is not a RCRA hazardous waste. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material

containing the product or derived from the product should be classified as a hazardous waste. (40CFR 261.20-24)

Waste Code No.:

Check re-use as alternative.

Contaminated packages and containers:

Emptied, but contaminated packages and containers may be recycled

Waste Code No.: 18715 (Germany)

# 14. TRANSPORT INFORMATION

International:

Land transport: ADR/RID/GGVS/GGVE: Not Regulated Sea transport: IMDG/GGV See UN-No.: Not Regulated



# 江 苏 宇 星 科 技 有 限 公 司 YUXING PIGMENT CO., LTD

Air transport: ICAO/IATA UN/ID-No.: Not Regulated

U.S. D.O.T. Classification: Not Regulated CANADA Transport of dangerous goods: Not Regulated

DOT Shipping Name: None

Technical Shipping Name: Inorganic Oxide

DOT Hazardous Classification: Non-Regulated. This product is not classed as a dangerous

substance under the classification, Packaging and Labeling of Dangerous Goods Act.

DOT Hazard Class: Non-Regulated. DOT Identification Number: None DOT Labels required: None

DOT Placards required: None. No specific transportation precautions required.

UN Class: None UN/NA Number: None

# 15. REGULATORY INFORMATION

Labeling according to EEC Directives: Not regulated.

SARA SARA 312:

Health: Immediate (Acute): No\* Fire: None Delayed (Chronic): No\*\* Reactivity: None

Sudden release of pressure: None

Not an acute hazard however may cause irritation due to abrasiveness.

These products are not classified as Carcinogens by the National Toxicology Program, the International Agency for Research on Cancer or the Occupational Safety and Health Administration. We do not know of any chronic health effect from these products. The finished pigment is a fine powder and may increase the risk of respiratory and skin disorders aggravated by dust.

The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/548/EEC or amendments.

Water risk class: WGK 0 (Self-assessment, acc. to § 7a 19,19a-1 of German Water Utilization Act (WHG).

# 16. FURTHER INFORMATION:

HMIS Codes: H=0,F=0,R=0,P=0 (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe) Vertical markings at left margin denote alterations of previous issue.

The information contained herein is based on the present state of our knowledge, but without liability, which is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the manufacturer. The data on this sheet relates only to the specific material designated herein. It may not be valid for this material responsibility to verify suitability and completeness of this information for their own particular use. The manufacturer assumes no legal responsibility for use or reliance upon these data.

Department issuing this data sheet: Product safety department